


Poly



Powerguard insurance global coverage

Within the first year, the output power shall not be less than 97.5% of the minimum output power in CSUN's product datasheet, thereafter the loss of output power shall not exceed 0.7% per year, ending with 80.7% in the 25th year.

■ CSUN ■ Standard warranty



CSUN310-72P

Standard Solar Product

CSUN310-72P
CSUN305-72P
CSUN300-72P
CSUN295-72P
CSUN290-72P

16.01%
Module efficiency

310 W
Highest power output

10 years
Material & workmanship warranty

25 years
Linear power output warranty



Industry leading conversion efficiency



Positive tolerance offer



Passed salt mist & ammonia corrosion, blowing sand and hail testing



Certificated to withstand wind (2400 Pa) and snow load (5400 Pa)



Excellent performance under weak light conditions



Good temperature coefficient enables better output in hot climates

- CSUN, established in 2004, is a high-tech corporation with its core business in R&D, manufacturing, and sale of high efficiency silicon based solar cells and modules.
- As one of the leading PV enterprises in the world, CSUN has delivered more than 1.4GW solar products, to residential, commercial, utility and off-grid projects all around the world.
- Through strict selection of raw materials, stringent quality control and tests in state of the art facilities in Istanbul, Nanjing and Shanghai, CSUN has always committed to higher efficiency, more stable and better cost performance products.

* Note: All specifications, warranties, certifications about module of „CSUN“ series also apply to that of „SST“.

All information and data are subject to change without notice and are provided without liability.



www.csun-solar.com



All rights reserved by CSUN
Version 1/2015-ENG

Electrical characteristics at Standard Test Conditions (STC)

Module	CSUN 310-72P	CSUN 305-72P	CSUN 300-72P	CSUN 295-72P	CSUN 290-72P
Maximum Power - Pmpp (W)	310	305	300	295	290
Positive power tolerance	0~3%	0~3%	0~3%	0~3%	0~3%
Open Circuit Voltage - Voc (V)	44.8	44.7	44.5	44.4	44.3
Short Circuit Current - Isc (A)	9.04	8.97	8.91	8.83	8.75
Maximum Power Voltage - Vmpp (V)	36.1	35.9	35.8	35.7	35.6
Maximum Power Current - Imp (A)	8.58	8.50	8.37	8.26	8.15
Module efficiency	16.01%	15.75%	15.49%	15.23%	14.98%

Electrical data relates to standard test conditions (STC) : irradiance 1000W /m² ; AM 1.5 ; cell temperature 25°C measuring uncertainty of power is within ±3%. Certified in accordance with IEC61215, IEC61730-1/2 and UL 1703

Electrical Characteristics at Nominal Operating Cell Temperature (NOCT)

Module	CSUN 310-72P	CSUN 305-72P	CSUN 300-72P	CSUN 295-72P	CSUN 290-72P
Maximum Power - Pmpp (W)	228	225	220	217	213
Maximum Power Voltage - Vmpp (V)	33.4	33.2	32.9	32.5	32.3
Maximum Power Current - Imp (A)	6.83	6.77	6.71	6.67	6.59
Open Circuit Voltage - Voc (V)	41.4	41.3	41.1	41.0	40.8
Short Circuit Current - Isc (A)	7.29	7.24	7.19	7.01	6.95

Electrical data relates to nominal operating cell temperature (NOCT): irradiance 800W /m²; wind speed 1 m/s ; cell temperature 45°C; ambient temperature 20°C measuring uncertainty of power is within ±3%.

Temperature Characteristics

Voltage Temperature Coefficient	-0.292%/K
Current Temperature Coefficient	+0.045%/K
Power Temperature Coefficient	-0.408%/K

Maximum Ratings

Maximum system voltage (V)	1000
Series fuse rating (A)	20
Reverse current overload (A)	27

Mechanical Characteristics


Dimensions	1956 × 990 × 50 mm
Weight	22.3 kg
Frame	Anodized aluminum profile
Front glass	White toughened safety glass, 3.2 mm
Cell Encapsulation	EVA (Ethylene-Vinyl-Acetate)
Back Sheet	Composite film
Cells	6 × 12 pieces polycrystalline solar cells series strings (156 × 156 mm)
Junction Box	Rated current ≥ 12A, IP ≥ 65, TUV & UL
Cable	Length 900 mm, 1 × 4 mm²
Connector	MC 4/ compatible with MC 4

System Design

Temp. range	-40°C to + 85°C
Hail	Max. diameter of 25mm with 23m/s impact speed
Max. capacity	Snow 5400 Pa, wind 2400 Pa
Application class	A
Safety class	II

Dimensions

Note: All dimensions in mm (inch)



IV-Curves

